

LOW COST DRILLING



ADVANTAGES

- Individual Model and Configuration choice (based on "LEGO" principle for minimization of spares).
- Best performance and weight to balance ratio.
- Perfect quality and customer service.
- Low noise and vibration level.
- Highest safety levels (ATEX, CE certification).
- Excellent durability and short pay-off period.
- 100 % parts interchangeabilities.
- All parts always on stock with short delivery times.
- Designed for use in mining, civil construction quarries and tunneling.
- Made according to precise engineering and quality standards.



LIGHT AND EFFECTIVE



Company organization is based on **ISO 9001:2008**. This is the ultimate level for optimal engineering standards within our company and of consistent product quality.

Acquired certificates for **CE, ATEX, GOST**. Confirmation of strict technical standards in connection with health and safety regulations have been approved.

MFD 90 ROCK DRILL FAMILY CONFIGURATION IN THREE MODELS:

MFD 90 with stroke 45 mm: more rotation for softer ground conditions.

MFD 90 MAX with stroke 60 mm: higher impact energy, less rotation for medium ground conditions.

MFD 90 MAX PLUS with stroke 60 mm: heavier piston for hard rock ground conditions.

TECHNICAL DATA FOR MFD 90 Piston stroke 45 mm

Conf.	Order No.	Piston Diameter	Impact rate	Free speed	Air consum. at 5 bar	Operating pressure	Net weight	Air connection	Length max.	Shank hex.	Vibration level according to ISO 8662 m/s ²	Sound pressure level according to ISO 11201 ** 105 dBA
DI	9 307 01L	90 mm	3100 min ⁻¹	320 rpm	4,5 m ³ /min	5-7 bar	26 kg	BSP 1"	680 mm	S 22	23	
C	9 307 02L	90 mm	3100 min ⁻¹	320 rpm	4,5 m ³ /min	5-7 bar	26 kg	BSPT 3/4"	680 mm	S 22	23	
CL	9 307 04L	90 mm	3100 min ⁻¹	320 rpm	4,5 m ³ /min	5-7 bar	26 kg	BSPT 3/4"	685 mm	S 22	23	

TECHNICAL DATA FOR MFD 90 MAX Piston stroke 60 mm

Conf.	Order No.	Piston Diameter	Impact rate	Free speed	Air consum. at 5 bar	Operating pressure	Net weight	Air connection	Length max.	Shank hex.	Vibration level according to ISO 8662 m/s ²	Sound pressure level according to ISO 11201 ** 105 dBA
DI	9 307 05L	90 mm	2750 min ⁻¹	300 rpm	4,5 m ³ /min	5-7 bar	26,30 kg	BSP 1"	695 mm	S 22	23	
C	9 307 08L	90 mm	2750 min ⁻¹	300 rpm	4,5 m ³ /min	5-7 bar	26,30 kg	BSPT 3/4"	695 mm	S 22	23	
CL	9 307 09L	90 mm	2750 min ⁻¹	300 rpm	4,5 m ³ /min	5-7 bar	26,30 kg	BSPT 3/4"	700 mm	S 22	23	
DIQ	9 307 05 017L	90 mm	2750 min ⁻¹	300 rpm	4,5 m ³ /min	5-7 bar	26,10 kg	BSP 1"	600 mm	S 22	23	
QA	9 307 25L	90 mm	2750 min ⁻¹	300 rpm	4,5 m ³ /min	5-7 bar	24,50 kg	BSP 1"	600 mm	S 22	23	
Q	9 307 28L	90 mm	2750 min ⁻¹	300 rpm	4,5 m ³ /min	5-7 bar	24,50 kg	BSP 1"	620 mm	S 22	23	
ST	9 307 32L	90 mm	2750 min ⁻¹	300 rpm	4,5 m ³ /min	5-7 bar	25,8+12 kg	BSPT 3/4"	620 mm	S 22	23	
SI	9 307 35L	90 mm	2750 min ⁻¹	300 rpm	4,5 m ³ /min	5-7 bar	26,30 kg	BSPT 3/4"	665 mm	S 22	7	
SIP	9 307 44L	90 mm	2750 min ⁻¹	300 rpm	4,5 m ³ /min	5-7 bar	27,30 kg	BSPT 3/4"	720 mm	S 25	3,9	

TECHNICAL DATA FOR MFD 90 MAX PLUS Piston stroke heavy 60 mm

Conf.	Order No.	Piston Diameter	Impact rate	Free speed	Air consum. at 5 bar	Operating pressure	Net weight	Air connection	Length max.	Shank hex.	Vibration level according to ISO 8662 m/s ²	Sound pressure level according to ISO 11201 ** 105 dBA
DI	9 307 13L	90 mm	2650 min ⁻¹	290 rpm	4,5 m ³ /min	5-7 bar	26,50 kg	BSP 1"	695 mm	S 22	23	
C	9 307 14L	90 mm	2650 min ⁻¹	290 rpm	4,5 m ³ /min	5-7 bar	26,50 kg	BSPT 3/4"	695 mm	S 22	23	
CL	9 307 15L	90 mm	2650 min ⁻¹	290 rpm	4,5 m ³ /min	5-7 bar	26,50 kg	BSPT 3/4"	700 mm	S 22	23	
SI	9 307 06L	90 mm	2650 min ⁻¹	290 rpm	4,5 m ³ /min	5-7 bar	26,50 kg	BSPT 3/4"	665 mm	S 22	7	
ST	9 307 07L	90 mm	2650 min ⁻¹	290 rpm	4,5 m ³ /min	5-7 bar	26+12 kg	BSPT 3/4"	620 mm	S 22	23	

** FOR POLYMER SILENCED (PS) CYLINDER HOUSING; FOR RELATIVE PRESSURE OF MEASUREMENT 4,5 BAR.

CERTIFICATION ACCORDING TO 94/9/EC DIRECTIVE (ATEX) MEETS: CE, DIN, GOST-R STANDARDS.

ADDITIONAL PARTS AVAILABLE FOR MODIFICATION TO ALL MODELS & VERSIONS.

FOR COAL MINES REQUEST ATEX ONLY!



MFD 90 ROCK DRILL FAMILY CONFIGURATION

Every model is available in various configurations: C, CL, DI, DIQ, ST, SI, SIP, QA, Q.

A PS (polymer silenced) modification (MAX, MAX PLUS model) is used in coal mines (ATEX certified) or as supreme double silenced variant. For standard drilling we offer common left hand rotation and for rock bolting right hand rotation. Flushing is by water entering through water inlet port. In case of air flushing compressed, air can be connected on water inlet, or we can supply a special air valve in (QA, SIA) configuration.

Standard shanks available are: S22 X 108 and S25 X 108.

For best efficiency and operators comfort choice, contact our technical sales department.

MFD 90 ROCK DRILL FAMILY CONFIGURATION



C CONFIGURATION

- Central operation of Air Leg from handle
- Right hand operating lever
- With mounting mechanism for DTC or PN 67/1000C,1300C Air Legs
- Simple fixation of Air Leg



CL CONFIGURATION

- Central operation of Air Leg from handle
- Left hand operating lever
- With mounting mechanism
- For DTC or PN 67/1000C,1300C Air Leg



DI CONFIGURATION

- D - handle
- I - independent Air Leg control
- Integrated mounting attachment for DT or PN67/1000,1300 Air Leg
- Right hand operating lever (can be modified to left hand)



DIQ CONFIGURATION

- Support plate for fixation
- Air can be connected to water inlet port
- Drilling on drill mast
- Side positioned water & air inlet ports



SI CONFIGURATION

- Ergonomic handle (7,5 m/s²)
- Detachable counter weights available
- with air flushing option (SIA) or;
- water flushing option (SI)



SIP CONFIGURATION

- Ergonomic handle (7,5 m/s²)
- Push / Pull vibration absorbing
- with air flushing option (SIA) or;
- water flushing option (SI)

MFD 90 ROCK DRILL FAMILY CONFIGURATION

STOPER CONFIGURATION

- Left hand back head
- Flange for Stopper Leg
- Control mechanism fixed in central cover



STINGER CONFIGURATION

- STOPER set up
- Retractable Air Leg
- Drilling downwards
- Mine shaft drilling with support or stage



CPSW CONFIGURATION

- Central operating of Air Leg from handle
- Special Air Leg attachment
- Right hand operating lever
- With mounting mechanism for DTC or PN67/1000C, 1300C Air Leg



QPS CONFIGURATION

- To be mounted on to slide frame
- Top air & water inlet port
- Integrated and polymer silencer
- Adaptable to other models



QPSW CONFIGURATION

- Complete drill mast frame
- Top water & air inlet port
- Double silenced
- Adaptable to other models

VK 23 ROCK DRILLS



VK 23DI

- With air or water valve
- Right hand operating lever
- With airleg mounting attachment
- Rifle bar rotation mechanism
- Cost saving and efficient



VK 23SIA

- With air (SIA) or water flushing option (SI)
- Right hand operating lever
- Antivibration sinker handle
- Push absorbing handle
- Push and pull absorbing handle (SIP)



VK 23T

- Firm handle Sinker Drill
- Low maintenance requirement
- Without Air Leg adapter
- Simple and light weight

VK 23 Rock Drills have rifle bar rotation system. Available with standard S22 X 108 or S25 x 108 tool shank (available on request).

TECHNICAL DATA FOR VK ROCK DRILLS

Conf.	Order No.	Piston Diameter	Impact rate	Free speed	Air consum. at 5 bar	Operating pressure	Net weight	Connection Air Water	Length max.	Shank	Vibration level according to ISO 8662 m/s ²	Sound pressure level according to ISO 11201 113 dBA
DI	9 302 14	65 mm	2100 min ⁻¹	220 rpm	2,5 m ³ /min	5-7 bar	23 kg	R 3/4" 1/2"	650 mm	S 22	18	
SIA	9 302 15	65 mm	2100 min ⁻¹	220 rpm	2,5 m ³ /min	5-7 bar	24 kg	R 3/4" -	650 mm	S 22	5	
SI	9 302 16	65 mm	2100 min ⁻¹	220 rpm	2,5 m ³ /min	5-7 bar	24 kg	R 3/4" 1/2"	650 mm	S 22	5	
T	9 302 20	65 mm	2100 min ⁻¹	220 rpm	2,5 m ³ /min	5-7 bar	21 kg	R 3/4" 1/2"	650 mm	S 22	18	



PN SINGLE STAGE & DT DOUBLE TELESCOPIC AIR LEG

TECHNICAL DATA FOR PN, DT

Air Leg Models	Part. Number	Rock Drill (handle) Type	Length retracted	Stroke	Length extendet	Piston diameter	Automatic retraction	Weight
PN 67/800 ST	9 338 10 001	MFD90ST,STO,ST-SI	1067 mm	800 mm	1867 mm	67 mm	no	11,30 kg
PN 67/1300 DI		MDF90DI	1880 mm	1282 mm	3162 mm	67 mm	yes	17,50 kg
PN 67/1300 DIM *		MFD90DI-PS	1880 mm	1282 mm	3162 mm	67 mm	yes	19,30 kg
PN 67/1000 DI		MFD90DI	1597 mm	1000 mm	2597 mm	67 mm	yes	15,80 kg
PN 67/1000 DIM *		MFD90DI-PS	1597 mm	1000 mm	2597 mm	67 mm	yes	17,20 kg
PN 67/1300 C		MFD90C,CL	1651 mm	1282 mm	2933 mm	67 mm	yes	15,00 kg
PN 67/1300 CM *		MFD90C-PS,CL-PS	1651 mm	1282 mm	2933 mm	67 mm	yes	16,90 kg
PN 67/1000 C		MFD90C,CL	1369 mm	1000 mm	2369 mm	67 mm	yes	13,50 kg
PN 67/1000 CM *		MFD90C-PS,CL-PS	1369 mm	1000 mm	2369 mm	67 mm	yes	14,80 kg
PN 53/1000		VK23DI	1445 mm	1020 mm	2465 mm	53 mm	no	11,50 kg
PN 53/1000 M *		VK23DI	1445 mm	1020 mm	2465 mm	53 mm	no	14,75 kg
PN 53/1300		VK23DI	1745 mm	1320 mm	3065 mm	53 mm	no	13,00 kg
PN 53/1300 M *		VK23DI	1745 mm	1320 mm	3065 mm	53 mm	no	16,48 kg
DTC 50	64-979-005-C	MFD90C,CL	740 mm	545 mm	1285 mm	78/65 mm	no/yes	10,50 kg
DTC 100	64-979-010-C	MFD90C,CL	965 mm	1040 mm	2005 mm	78/65 mm	no/yes	12,00 kg
DTC 140	64-979-014-C	MFD90C,CL	1170 mm	1440 mm	2610 mm	78/65 mm	no/yes	14,50 kg
DTC 180	64-979-018-C	MFD90C,CL	1370 mm	1840 mm	3210 mm	78/65 mm	no/yes	16,00 kg
DTC 200	64-979-020-C	MFD90C,CL	1510 mm	2100 mm	3610 mm	78/65 mm	no/yes	17,00 kg
DT 50	64-979-005-DM	MFD90DI	890 mm	545 mm	1435 mm	78/65 mm	no/yes	12,00 kg
DT 100	64-979-010-DM	MFD90DI	1115 mm	1040 mm	2155mm	78/65 mm	no/yes	13,50 kg
DT 140	64-979-014-DM	MFD90DI	1320 mm	1440 mm	2760 mm	78/65 mm	no/yes	15,00 kg
DT 180	64-979-018-DM	MFD90DI	1520 mm	1840 mm	3360 mm	78/65 mm	no/yes	17,00 kg
DT 200	64-979-020-DM	MFD90DI	1660 mm	2100 mm	3760 mm	78/65 mm	no/yes	18,50 kg

* STEEL METAL COVERED CYLINDER WITH **ATEX** CERTIFICATION



DOUBLE TELESCOPIC AIR LEGS

- DTC and DT (Double Telescopic) Air Legs are light weight and robust
- All have long stroke and retractable second stage
- DTC model for MFD 90C and CL.
- DT model for MFD 90DI and VK 23DI.
- DTS double telescopic STOPER on request

SINGLE STAGE AIR LEGS

- PN 67/1000, 1300 DI, DIM fully retractable, extension from top
- PN 67/1000, 1300 C, CM fully retractable, extension from bottom
- PN 53/1000, 1300; PN 53/1000, 1300 M extension from top
- M - steel/metal covered - ATEX
- STINGER Air Leg for vertical downward drilling on request



SPARE AND WEARING PARTS MADE FROM HIGH RESISTENT MATERIALS

100% PARTS INTERCHANGEABILITY - ALL PARTS AVAILABLE IN STOCK - SHORT DELIVERY TERMS

HWR PISTON STROKE 45, 60, 60 HEAVY

- Excellent wear, heat and corrosion resistance
- Striking end can be refaced by grinding (max 1 mm)
- Left or right rotation



TWO PIECE RATCHET RING

- Threaded design for cost saving
- Forged materials used for reliability



POLYMER CYLINDER HOUSING WITH DISPERSED EXHAUST CYLINDER LINER

- New benchmark in noise reduction
- For 60 mm piston stroke
- MAX and MAX PLUS models available
- Certified according to 94/9/EC directive (ATEX)
- Meets CE,DIN,GOST Standards



INTEGRALS, REAMERS, TAPER RODS

- Drilling of natural stones and concrete
- Hexagonal shank 22 x 108 or 25 x 108
- Diameters and lengths according to ISO or (as agreed)



IN LINE LUBRICATORS MAZ 10(M), 20(M), 30(M), 40(M)

- If oil runs out, the compressed air supply automatically closes
- Reliable operation is guaranteed
- Safety off function if air disconnects
- M - steel/metal covered with ATEX certificate for coal mines



Lubricator Order No.	MAZ 10 (M) 9 336 01 (05)	MAZ 20 (M) 9 336 02 (06)	MAZ 30 (M) 9 336 03 (07)	MAZ 40 (M) 9 336 04 (08)
Lenght (mm)	404	404	404	404
Width (mm)	128	128	128	128
Weight (kg)	4,8	4,8	4,8	4,8
Oil quantity in tank (l)	0,5	0,5	0,5	0,5
Working pressure (bar)	4-7	4-7	4-7	4-7
Air flow (min ³)	0,5-1	1-2,5	2,5-4,8	4,8-7
Connection thread (external)	R3/4"	R3/4"	R1"	R1"

OPREMA RECOMMENDATION:

MAZ 10 (M) use with: NP100, NP180, CK30

MAZ 20 (M) use with: LRK7, LRK8, SRK12, SRK17
ECO17, ECO20, ECO23,
TRK30

MAZ 30 (M) use with: VK23

MAZ 40 (M) to be use with: MFD90, MFD90 MAX,
MFD90 MAX PLUS,
LPB, LTV